

9601

SBD TRANSCEIVER



9601 SBD Transceiver

The 9601 SBD Transceiver combines the global coverage of the Iridium satellite constellation with the low latency of the Iridium Short Burst Data Service (SBD) in a small, lowcost transceiver design. The 9601 is a lower cost, Iridium Satellite LLC manufactured product designed as an OEM module for integration into applications that only use the Iridium Short Burst Data Service. Short Burst Data applications are supported through an RS232 interface.



21 Thornhill Drive, Dartmouth, Nova Scotia, CANADA B3B 1R9
Tel: +1-902-405-4428 / Fax: +1-902-405-4438
sales@joubeh.com / www.joubeh.com



9601

SBD TRANSCEIVER

Key Features

- Single Header Connector for:
 - Power
 - On/Off Control
 - RS232 9-wire Interface
 - Network Available
- SMA Antenna Connector to connect to small omni directional L-Band antennas
- Simple AT Command Interface

Capabilities:

Iridium Short-Burst Data (SBD) Service provides:

- Mobile Originated messages up to 340 bytes
- Mobile Terminated messages up to 270 bytes
- Low, uniform global latency (less than 1 minute)
- Coverage in areas not served by cellular



Technical Specifications

Mechanical

Length (without antenna connector):	106.4 mm
Width:	56.2 mm
Height (not including user interface connector):	13 mm
Weight:	117g

Environmental

Operating Temperature Range:	-35°C to +70°C
Operating Humidity Range:	75% RH
Storage Temperature Range:	-40°C to +85°C
Storage Humidity Range:	93% RH

RF Interface

Frequency range:	1616MHz to 1626.5MHz
Duplexing method:	TDD (Time Domain Duplex)
Oscillator stability:	± 1.5ppm
Antenna VSWR:	1.5:1(50 ohms)
Multiplexing method:	TDMA/FDMA

DC Power Interface

Main input voltage -nominal:	5.0 V DC ± 0.5V DC
Main input voltage - ripple:	40 mVpp
Peak input current @ 5V(maximum):	1.5 A
Input current @ 5V (average):	350mA (See Note 1)
Input standby current @ 5V (average):	66 mA

Iridium limits distribution of the Transceiver equipment to approved Iridium VARs and VAMs.

Specifications are subject to change without notice. Additional information to that contained herein may be required in order to develop a fully operational unit incorporating the 9601. The specifications provided herein are for informational purposes only.

Note 1: This is the current consumption when a SBD message transfer is in process. The average power consumption depends on the view of the satellite constellation from the antenna.



Innovative Global Telematic Solutions

21 Thornhill Drive, Dartmouth, Nova Scotia, CANADA B3B 1R9
Tel: +1-902-405-4428 / Fax: +1-902-405-4438 / sales@joubeh.com / www.joubeh.com